

## FF Wax

**Microcement floor maintenance wax for indoor use.**

### DESCRIPTION

**FF Wax** is a product based on waxes and acrylics, which, when applied, creates a waterproof, protective and maintenance coating. The coating is hard, abrasion resistant and has an anti-slippery effect. The product is intended for varnished surfaces, including microcement floors. It works very well as an additional coating protection. It can be successfully used as a sealer restorer.

The product is odorless, vapor-permeable, resistant to polishing and alcohol disinfection.

### APPLICATION

Before applying the product, the surface must be dry (less than 3% humidity) and thoroughly dusted and washed. Shake the container with the **FF Wax** well. The product is ready-to-use, it should not be diluted. Apply in sections, using a microfiber mop in 2-3 thin layers. The drying time between coats is at least 60 minutes. Additional polishing, increasing the gloss, can be done with a soft pad after the surface is completely dry (2-3 days).

Do not use outdoors - the product is sensitive to low temperatures.



### TECHNICAL DATA

- Consumption of the product depends on the surface, method of application, and for one layer it is approx: 1-3 l per 100 m<sup>2</sup>
- Color: milky
- pH: 8.0-9.0
- Shelf life: 24 months in unopened original packaging (store above 15 °C, protect against frost and direct sunlight).
- Application temperature: +15°C ÷ +25°C
- Gloss level: available in both satin and gloss

### PACKAGING

FF Wax is available in packages of 1l.

### SAFETY AND HEALTH

Observe the general health and safety rules and other rules contained in the safety data sheet.

The product is a non-hazardous substance, is not hazardous during transport, has not been classified in any toxicity class, and does not require special precautions for storage.

The product is a mixture of the highest quality ingredients, mainly: waxes, acrylics, surfactants, solvents and preservatives.



@festfloor

hello@festfloor.com  
+48 537 991 307  
www.festfloor.com

