**TECHNICAL DATA SHEET** 

# **FF FIX PRO**

# Conservation agent for floors



# **DESCRIPTION**

**FF FIX PRO** is a polyurethane resin-based product for the maintenance of particularly damaged and heavily trafficked wooden, resin, microcement and resilient floors such as LVT, PVC or linoleum. It leaves a matt finish.

### **APPLICATION**

Shake thoroughly before use.

Ensure that the surface is dry, degreased and cleaned of wax and dust. Then clean the surface with **FESTCleaner** according to the instructions. Once the surface has been cleaned, you can proceed with the application of **FF FIX PRO**. Wipe the floor gently with a cloth and water, pour a small amount of **FF FIX PRO** on and proceed with the application, taking care to distribute the product evenly without leaving an excessive amount on the working surface.

# **CAUTIONS**

Re-use of the floor can be started after 2-3h. Avoid moving furniture and carpets before 12-24h after application. The next cleaning can be carried out after three days using suitable detergents.

A preliminary test is recommended to check the adhesion to the substrate.

## **TECHNICAL DATA**

- Consumption: 1I 40-60 m<sup>2</sup>
- Storage stability: 1 year in original sealed containers at +10°C to +25°C.

#### **PACKAGING**

FF FIX PRO is available in 1l bottle.

### SAFETY AND HEALTH

WARNING: Keep out of the reach of children. Have the product packaging or label at hand in case you need to seek medical advice.



