

# FESTGrunt

**Fast drying, synthetic resin based primer  
for absorbent substrates**



## DESCRIPTION

Acrylic surface primer, reducing and equalizing absorbency of the substrate, improving adhesion. Ideal for priming before plastering and flooring works (microcement, plaster, mosaic plasters, organic plasters etc.). Can be used on cementitious, gypsum, anhydrite surfaces, tiles, etc. Do not apply onto magnesium substrates. **FESTGrunt** does not waterproof gypsum substrates even though it considerably reduces their porosity and absorption.

## PRODUCT ADVANTAGES

- primes the substrate
- reduce substrate porosity and prevents the absorption of water from the mortar
- increases the adhesion of the mortar to the substrate
- improves the flow of self-leveling mortars
- vapor permeable

## HOW TO USE

The substrate must be solid, clean, dry and free from oils, grease, residual paint and other loose materials.

Before application **FESTGrunt** should be stir briefly. Apply uniformly in plentiful quantity using a roller or a brush.

On uneven or very absorbent surfaces it is recommended to apply **FESTGrunt** in several layers. Leave to dry for 2-4h.

Once dry, further work can be started.

## SAFETY AND HEALTH

Product for professional users only. Read technical sheets of all components of the system available on [www.festfloor.com](http://www.festfloor.com). May be irritating to the skin. May cause eye damage. May cause an allergic skin reaction. Use protective gloves / protective clothing / eye protection / face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice / attention. Dispose of contents / container in accordance with local regulations. Keep out of the reach of children.

## TECHNICAL DATA

- Consumption: 0,1 - 0,3 kg/m<sup>2</sup> - depending on the absorbency of the substrate
- Color: milky
- Density: 1,0 g/cm<sup>3</sup>
- pH: 8
- Application temperature range: from +15°C to +25°C
- Drying time: 2-4 hours
- Shelf life and storage conditions: 12 months in original unopened container. Protect from frost.

## PACKAGING

**FESTGrunt** is available in containers of:

- 1l,
- 5l.

## CLEANING OF TOOLS

Cleaning of tools should be carried out with water.



@festfloor

hello@festfloor.com  
+48 537 991 307  
www.festfloor.com

