

## FF Wax Care

Microcement floor maintenance wax for interior use.

### DESCRIPTION

**FF WAX CARE** is a water-resistant wax for the care of sealer, oiled and/or waxed wood, microcement and stone floors. Its special formula renews and protects dull, scratched or damaged floors.

Product features:

- protects and preserves sealer
- creates a hydrophobic coating
- increases resistance to abrasion
- doesn't change the appearance of the sealer

### APPLICATION

Shake well before use. Apply FF WAX CARE by spraying it on the surface to be refreshed. Spread the product evenly with a cloth. Be careful not to leave excess product on the surface. After 30 minutes, when completely dry, polish the surface with a soft cloth or white pad. Perform regular maintenance by applying another coat of FEST WAX. It is not recommended to use rough and hard cloths for wax application.

**Note:** Using FF WAX CARE on poorly absorbent surfaces may increase slipperiness, especially in the presence of water or high humidity. Before using, it is recommended to perform a test on a small area. Prolonged exposure to temperatures below +10°C may cause the product to thicken. Store at temperatures above +15°C before use.



### TECHNICAL DATA

- Consumption: approx. 70-90 m<sup>2</sup>/L
- Color: transparent
- Application temperature: +10°C ÷ +25°C
- Curing time: 30 minutes\*
- Total cure: 12-24 h\*  
*\* At 20°C and 65% relative humidity.*
- Shelf life: 24 months in original, unopened packaging. Store at a temperature of +10°C to +25°C. Protect from frost and direct sunlight.

### PACKAGING

The product is supplied in 500 ml packaging.

### SAFETY AND HEALTH

Protect from frost during transport and storage. Avoid prolonged exposure to temperatures below +10°C. Keep away from children. Keep container or product label handy in case of medical advice.

EUH066 Repeated exposure may cause skin drying and cracking. EUH210 Safety data sheet available on request. P260 Do not breathe dust/fume/gas/mist/vapour/spray. P271 Use only outdoors or in a well-ventilated area.



@festfloor

hello@festfloor.com  
+48 537 991 307  
www.festfloor.com

